



Bearing No. 21313-E1-K + AH313G

	AH313G / Designation, withdrawal sleeve
l	42 mm
a	3 mm
m	2,13 kg / Weight
d	65 mm
e	0,22
b	8 mm
B	33 mm
D	140 mm
Size (mm)	60x140x33
Width (mm)	33
Y <sub>2</sub>	4,67
Y <sub>1</sub>	3,14
Y <sub>0</sub>	3,07
C <sub>r</sub>	250000 N
m <sub>1</sub>	0,23 kg / Weight, withdrawal sleeve
n <sub>G</sub>	6200 1/min / Limiting speed
n <sub>B</sub>	4200 1/min / Reference speed
d <sub>s</sub>	3,2 mm
n <sub>s</sub>	6,5 mm
d <sub>2</sub>	94,9 mm
D <sub>1</sub>	126,8 mm
d <sub>2G</sub>	M70X2
d <sub>1H</sub>	60 mm
C <sub>0r</sub>	270000 N / Static load rating (radial)

Bearing number	21313-E1-K + AH313G
$r_{\min}$	2,1 mm
$r_{a \max}$	2,1 mm
$d_{a \min}$	77 mm
$D_{a \max}$	128 mm
Bore Diameter (mm)	60
Outer Diameter (mm)	140