



Bearing No. 7316B

a	71.9 mm
d	80 mm
D	170 mm
B	39 mm
C	39 mm
Cr	169
f0	-
Cu	6.35
C0r	109
Noun	Bearing
Bore	3.15 Inch 80 Millimeter
Width	1.535 Inch 39 Millimeter
a(mm)	71.9
r min.	2.1 mm
UNSPSC	31171531
r(min)	2.1
Weight	3.85 Kg
da(min)	92
ra max.	2 mm
r1 min.	1.1 mm
Da max.	158 mm
r1(min)	1.1
da min.	92 mm
Da(max)	158
ra(max)	2
Category	Angular Contact Ball Bearing
Oil lub.	3700
Inventory	0.0
Enclosure	Open

Size (mm)	80x170x39
Snap Ring	No
Width (mm)	39
Grease lub.	2800
Bearing No.	7316B
Flush Ground	No
Contact Angle	40 Degree
Cage Material	Steel
Inch - Metric	Metric
Product Group	B00308
Keyword String	Angular Contact
Bearing number	7316B
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Angle (?)	40 °
(Refer.)Mass(kg)	3.85
Outside Diameter	6.693 Inch 170 Millimeter
Manufacturer URL	http://www.koyousa.com
Long Description	80MM Bore; 170MM Outside Diameter; 39MM Width; Open; No Flush Ground; Ball Bearing; Single Row of Balls; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; C0-Medium; Steel Cage; 40 Degree; 1 (Single)
Weight / Kilogram	0
Manufacturer Name	KOYO
Number of Bearings	1 (Single)
Internal Clearance	C0-Medium
Bore Diameter (mm)	80
Outer Diameter (mm)	170

Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.28
Number of Rows of Balls	Single Row
(Grease) Lubrication Speed	3500 r/min
Maximum Capacity / Filling Slot	No