



### Bearing No. 6213

D	120 mm
d	65 mm
B	23 mm
C	23 mm
f0	14.4
Cu	2.65
Cr	71.5
C0r	40.1
Bore	2.559 Inch   65 Millimeter
Noun	Bearing
UNSPSC	31171504
Weight	0,99 Kg
r(min)	1.5
r min.	1,5 mm
da min.	73 mm
ra(max)	1.5
Da max.	112 mm
Da(max)	112
da(min)	73
ra max.	1,5 mm
Category	Single Row Ball Bearing
Oil lub.	6400
Inventory	0.0
Enclosure	Open
Size (mm)	65x120x23
Snap Ring	No
Width (mm)	23
Grease lub.	5400
Bearing No.	6213

Weight / LBS	2.378
Product Group	B00308
Cage Material	Steel
Inch - Metric	Metric
Keyword String	Ball
Bearing number	6213
Precision Class	ABEC 1   ISO P0
Rolling Element	Ball Bearing
Outer Race Width	0.906 Inch   23 Millimeter
Long Description	65MM Bore; 120MM Outside Diameter; 23MM Outer Race Diameter; Open; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Outside Diameter	4.724 Inch   120 Millimeter
(Refer.)Mass(kg)	0.990
Manufacturer URL	<a href="http://www.koyousa.com">http://www.koyousa.com</a>
Weight / Kilogram	1.08
Manufacturer Name	KOYO
Internal Clearance	C0-Medium
Bore Diameter (mm)	65
Outer Diameter (mm)	120
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
(Oil) Lubrication Speed	6400 r/min
Manufacturer Item Number	6213
Internal Special Features	No
(Grease) Lubrication Speed	5400 r/min

Basic static load rating (C0)	40,1 kN
Basic dynamic load rating (C)	57,2 kN
Maximum Capacity / Filling Slot	No