



Bearing No. 6213

D	120 mm
d	65 mm
B	23 mm
C	23 mm
r	1.5
Z_	10
C0	40
ra	1.5
fo	14.4
D_	120
B_	23
DI_	75.831
SRI	8.63
DE_	109.169
DA_	16.669
SRE	8.63
D_a	112
Bore	2.559 Inch 65 Millimeter
SRIX	0.03
Noun	Bearing
yobi	6213
SDM_	92.5
bomp	0
SRIN	-0.03
mass	1
SREX	0.03
SBRG	2
KBRG	6101
SREN	-0.03

ALPHA_	0
UNSPSC	31171504
da max	80 mm
LangID	1
r min.	1,5 mm
C_conv	57500
Weight	1 Kg
da min	73
GRS rpm	5300
Oil rpm	6300
hidYobi	6213
da min.	73 mm
Da max.	112 mm
ra max.	1,5 mm
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Inventory	0.0
Snap Ring	No
Size (mm)	65x120x23
Enclosure	Open
bore type:	Round
Prod_Type3	DGBB_SR_OT
Width (mm)	23
Weight / LBS	1.02
maximum rpm:	6300 rpm
Product Group	B00308
closure type:	Open
Cage Material	Steel
Inch - Metric	Metric
Bearing number	6213
bore diameter:	65 mm
cage material:	Steel Cage

overall width:	23 mm
Keyword String	Ball
finish/coating:	Uncoated
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Outside Diameter	4.724 Inch 120 Millimeter
Manufacturer URL	http://www.nskamericas.com
Long Description	65MM Bore; 120MM Outside Diameter; 23MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Outer Race Width	0.906 Inch 23 Millimeter
Weight / Kilogram	0.997
Manufacturer Name	NSK
precision rating:	ABEC1, P0
outside diameter:	120 mm
Internal Clearance	C0-Medium
Bore Diameter (mm)	65
snap ring included:	Without Snap Ring
Outer Diameter (mm)	120
internal clearance:	C0
Minimum Buy Quantity	N/A
row type & fill slot:	Single Row Non-Fill Slot
dynamic load capacity:	57000 N
Harmonized Tariff Code	8482.10.50.68
(Oil) Lubrication Speed	6 300 r/min
Manufacturer Item Number	6213
Internal Special	No

Features	
(Grease) Lubrication Speed	5 300 r/min
Basic static load rating (C0)	40 kN
Basic dynamic load rating (C)	57,5 kN
Maximum Capacity / Filling Slot	No