



Bearing No. 6213-2NSE

D	120 mm
d	65 mm
B	23 mm
C	23 mm
Noun	Bearing
Bore	2.559 Inch 65 Millimeter
Width	23 mm
Weight	0.990 Kg
UNSPSC	31171504
r min.	1.5 mm
da min.	74 mm
Da max.	111 mm
ra max.	1.5 mm
Category	Single Row Ball Bearing
ra (max)	1.5 mm
da (min)	74 mm
Da (max)	111 mm
Factor fo	14.4
Size (mm)	65x120x23
Inventory	0.0
Bore Size	65 mm
Bore Type	Cylindrical Bore
Enclosure	2 Seals
Snap Ring	No
Width (mm)	23
Configuration	Single Row
Inch - Metric	Metric
Cage Material	Steel
Product Group	B00308

Bearing number	6213-2NSE
Enclosure Type	Contact Seal
Other Features	Deep Groove
Keyword String	Ball
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
Radial Clearance	0.008 to 0.028 mm
Outer Race Width	0.906 Inch 23 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Outside Diameter	4.724 Inch 120 Millimeter
Manufacturer URL	http://www.nachi-america.com
Long Description	65MM Bore; 120MM Outside Diameter; 23MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage;
Weight / Kilogram	0
Manufacturer Name	NACHI
Static Load Rating	40,000 N
Bore Diameter (mm)	65
Internal Clearance	C0-Medium
Outer Diameter (mm)	120
Dynamic Load Rating	57,000 N
Minimum Buy Quantity	N/A
Fillet Radius/Chamfer	1.5 mm
Harmonized Tariff Code	8482.10.50.68
Limiting Speed - Grease	3,600 rpm
Internal Special	No

Features	
Basic dynamic load rating (C)	57 kN
Basic static load rating (C0)	40 kN
Maximum Capacity / Filling Slot	No