



Bearing No. 6213LLU

D	120 mm
d	65 mm
B	23 mm
C	23 mm
Noun	Bearing
Bore	2.559 Inch 65 Millimeter
r min.	1,5 mm
da max	80,5 mm
Weight	0,99 Kg
UNSPSC	31171504
da min.	73 mm
series:	62
Da max.	112 mm
ra max.	1,5 mm
Category	Single Row Ball Bearing
Inventory	0.0
Enclosure	2 Seals
Snap Ring	No
Size (mm)	65x120x23
Width (mm)	23
bore type:	Round
Weight / LBS	2.18
maximum rpm:	6500 RPM
Product Group	B00308
closure type:	Double Sealed
Inch - Metric	Metric
Cage Material	Steel
overall width:	23 mm
Keyword String	Ball

fillet radius:	1.5 mm
Other Features	Deep Groove Double Lip Friction Nitrile Rubber Seal -20 To 120 Deg C Shell Alvania Prelubricated
Bearing number	6213LLU
Enclosure Type	Contact Seal
bore diameter:	65 mm
cage material:	Steel
Reference speed	3 600 r/min
Rolling Element	Ball Bearing
finish/coating:	Uncoated
Precision Class	ABEC 1 ISO P0
Inner Race Width	0 Inch 0 Millimeter
Outer Race Width	0.906 Inch 23 Millimeter
Outside Diameter	4.724 Inch 120 Millimeter
Long Description	65MM Bore; 120MM Outside Diameter; 23MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage;
Manufacturer URL	http://www.ntnamerica.com
Weight / Kilogram	0
outer ring width:	23 mm
Manufacturer Name	NTN
bearing material:	High Carbon Chrome Steel
inner ring width:	23 mm

precision rating:	ISO Class 0
outside diameter:	120 mm
Internal Clearance	C0-Medium
Bore Diameter (mm)	65
snap ring included:	Without Snap Ring
Outer Diameter (mm)	120
internal clearance:	CN
Minimum Buy Quantity	N/A
static load capacity:	40000 N
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm (grease):	3600 rpm
Harmonized Tariff Code	8482.10.50.68
dynamic load capacity:	57500 N
Internal Special Features	No
manufacturer product page:	Click here
operating temperature range:	-40 to 120 °C
Basic dynamic load rating (C)	57,5 kN
Basic static load rating (C0)	40 kN
Maximum Capacity / Filling Slot	No