



Bearing No. 6213NR

f	2,82 mm
r	1.5
d	65 mm
D	120 mm
B	23 mm
C	23 mm
a	4,06 mm
b	3,1 mm
D1	115,21 mm
fo	14.4
C0	40
ra	1.5
D2	129,7 mm
B_	23
Cy	6.5
Dx	131.5
rn	0,5 mm
ro	0.6
D_	120
Z_	10
SRE	8.63
D_a	112
SRI	8.63
DE_	109.169
DA_	16.669
DI_	75.831
bomp	0
SREX	0.03
yobi	6213NR
SBRG	2

KBRG	6101
SDM_	92.5
mass	1
Bore	2.559 Inch   65 Millimeter
SRIX	0.03
SRIN	-0.03
SREN	-0.03
Noun	Bearing
UNSPSC	31171504
LangID	1
r min.	1,5 mm
da max	80 mm
C_conv	57500
ALPHA_	0
Weight	1 Kg
da min	73
ra max.	1,5 mm
Da max.	112 mm
hidYobi	6213NR
Oil rpm	6300
da min.	73 mm
GRS rpm	5300
r0 max.	0,6 mm
hidTable	ecat_NSRDGB
Category	Single Row Ball Bearing
Snap Ring	Yes
Size (mm)	65x120x23
Inventory	0.0
Enclosure	Open
bore type:	Round
Width (mm)	23
Prod_Type3	DGBB_SR_NR_OT

Weight / LBS	0.995
closure type:	Open
Product Group	B00308
Cage Material	Steel
Inch - Metric	Metric
Bearing number	6213NR
Keyword String	Ball
bore diameter:	65 mm
overall width:	23 mm
Rolling Element	Ball Bearing
Precision Class	ABEC 1   ISO P0
Outer Race Width	0.906 Inch   23 Millimeter
Outside Diameter	4.724 Inch   120 Millimeter
Long Description	65MM Bore; 120MM Outside Diameter; 23MM Outer Race Diameter; Open; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; Yes Snap Ring; No Internal Special Features
Manufacturer URL	<a href="http://www.nskamericas.com">http://www.nskamericas.com</a>
outside diameter:	120 mm
Weight / Kilogram	0.95
Manufacturer Name	NSK
Internal Clearance	C0-Medium
Bore Diameter (mm)	65
Outer Diameter (mm)	120
internal clearance:	Normal Clearance
snap ring included:	Without Snap Ring
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68

(Oil) Lubrication Speed	6 300 r/min
manufacturer upc number:	029176034770
Manufacturer Item Number	6213NR
Internal Special Features	No
(Grease) Lubrication Speed	5 300 r/min
Basic static load rating (C0)	40 kN
Basic dynamic load rating (C)	57,5 kN
Maximum Capacity / Filling Slot	No