



Bearing No. 6213VV

D	120 mm
d	65 mm
B	23 mm
C	23 mm
r	1.5
Z_	10
B_	23
D_	120
ra	1.5
C0	40
fo	14.4
DI_	75.831
SRI	8.63
D_a	112
DE_	109.169
DA_	16.669
SRE	8.63
SRIN	-0.03
SBRG	2
yobi	6213VV
SDM_	92.5
SREX	0.03
KBRG	6151
bomp	0
mass	1
Bore	2.559 Inch 65 Millimeter
SRIX	0.03
SREN	-0.03
Noun	Bearing

ALPHA_	0
da min	73
LangID	1
r min.	1,5 mm
UNSPSC	31171504
da max	80 mm
C_conv	57500
Weight	1 Kg
ra max.	1,5 mm
hidYobi	6213VV
GRS rpm	5300
da min.	73 mm
Da max.	112 mm
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Snap Ring	No
Size (mm)	65x120x23
Enclosure	2 Seals
Inventory	0.0
Width (mm)	23
Prod_Type3	DGBB_SR_VV
Weight / LBS	0.995
Cage Material	Steel
Product Group	B00308
Inch - Metric	Metric
Bearing number	6213VV
Keyword String	Ball
Enclosure Type	Non-Contact Seal
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Outer Race Width	0.906 Inch 23 Millimeter
Outside Diameter	4.724 Inch 120

	Millimeter
Long Description	65MM Bore; 120MM Outside Diameter; 23MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Manufacturer URL	http://www.nskamericas.com
Weight / Kilogram	0.99
Manufacturer Name	NSK
Internal Clearance	C0-Medium
Bore Diameter (mm)	65
Outer Diameter (mm)	120
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6213VV
Internal Special Features	No
(Grease) Lubrication Speed	5 300 r/min
Basic static load rating (C0)	40 kN
Basic dynamic load rating (C)	57,5 kN
Maximum Capacity / Filling Slot	No