



Bearing No. 6213ZZ

D	120 mm
d	65 mm
B	23 mm
C	23 mm
rn	0,5 mm
Noun	Bearing
Bore	2.559 Inch 65 Millimeter
UNSPSC	31171504
da max	80,5 mm
Weight	0,99 Kg
r min.	1,5 mm
da min.	73 mm
Da max.	112 mm
ra max.	1,5 mm
series:	62
Category	Single Row Ball Bearing
Size (mm)	65x120x23
Enclosure	2 Metal Shields
Inventory	0.0
Snap Ring	No
bore type:	Round
Width (mm)	23
Weight / LBS	2.1847
maximum rpm:	6500 RPM
closure type:	Double Shielded
Product Group	B00308
Cage Material	Steel
Inch - Metric	Metric
Keyword String	Ball

Other Features	Deep Groove Shell Alvania Prelubricated
Bearing number	6213ZZ
bore diameter:	65 mm
overall width:	23 mm
cage material:	Steel
fillet radius:	1.5 mm
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
finish/coating:	Uncoated
Outer Race Width	0.906 Inch 23 Millimeter
Outside Diameter	4.724 Inch 120 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Long Description	65MM Bore; 120MM Outside Diameter; 23MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Ste
Manufacturer URL	http://www.ntnamerica.com
Weight / Kilogram	0
outer ring width:	23 mm
Manufacturer Name	NTN
bearing material:	High Carbon Chrome Steel
inner ring width:	23 mm
outside diameter:	120 mm
precision rating:	ISO Class 0
Internal Clearance	C0-Medium

Bore Diameter (mm)	65
Outer Diameter (mm)	120
internal clearance:	CN
snap ring included:	Without Snap Ring
Minimum Buy Quantity	N/A
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm (grease):	5500 rpm
static load capacity:	40000 N
Harmonized Tariff Code	8482.10.50.68
dynamic load capacity:	57500 N
Internal Special Features	No
(Grease) Lubrication Speed	5 500 r/min
manufacturer product page:	Click here
operating temperature range:	-40 to 120 °C
Basic static load rating (C0)	40 kN
Basic dynamic load rating (C)	57,5 kN
Maximum Capacity / Filling Slot	No