



**Bearing No. 6213ZZE**

D	120 mm
d	65 mm
B	23 mm
C	23 mm
Noun	Bearing
Bore	2.559 Inch   65 Millimeter
Width	23 mm
UNSPSC	31171504
r min.	1.5 mm
Weight	0.990 Kg
da min.	74 mm
Da max.	111 mm
ra max.	1.5 mm
Category	Single Row Ball Bearing
ra (max)	1.5 mm
Da (max)	111 mm
da (min)	74 mm
Factor fo	14.4
Inventory	0.0
Bore Size	65 mm
Bore Type	Cylindrical Bore
Enclosure	2 Metal Shields
Snap Ring	No
Size (mm)	65x120x23
Width (mm)	23
Configuration	Single Row
Product Group	B00308
Cage Material	Steel
Inch - Metric	Metric

Other Features	Deep Groove
Keyword String	Ball
Bearing number	6213ZZE
Precision Class	ABEC 1   ISO P0
Rolling Element	Ball Bearing
Long Description	65MM Bore; 120MM Outside Diameter; 23MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Ste
Manufacturer URL	<a href="http://www.nachiamerica.com">http://www.nachiamerica.com</a>
Outer Race Width	0.906 Inch   23 Millimeter
Inner Race Width	0 Inch   0 Millimeter
Outside Diameter	4.724 Inch   120 Millimeter
Radial Clearance	0.008 to 0.028 mm
Weight / Kilogram	0
Manufacturer Name	NACHI
Bore Diameter (mm)	65
Internal Clearance	C0-Medium
Static Load Rating	40,000 N
Dynamic Load Rating	57,000 N
Outer Diameter (mm)	120
Minimum Buy Quantity	N/A
Fillet Radius/Chamfer	1.5 mm
Harmonized Tariff Code	8482.10.50.68
Limiting Speed - Grease	5,500 rpm
Internal Special Features	No

Basic dynamic load rating (C)	57 kN
Basic static load rating (C0)	40 kN
Maximum Capacity / Filling Slot	No