



Bearing No. 7213B

D	120 mm
d	65 mm
B	23 mm
C	23 mm
a	50.3 mm
Cu	3.10
Cr	79.5
f0	-
C0r	52.6
Noun	Bearing
Bore	2.559 Inch 65 Millimeter
a(mm)	50.3
Width	0.906 Inch 23 Millimeter
Weight	1.02 Kg
r min.	1.5 mm
UNSPSC	31171531
r(min)	1.5
da(min)	73.5
r1 min.	1 mm
Da max.	111.5 mm
r1(min)	1
Da(max)	111.5
ra max.	1.5 mm
ra(max)	1.5
da min.	73.5 mm
Category	Angular Contact Ball Bearing
Oil lub.	5100
Inventory	0.0

Enclosure	Open
Size (mm)	65x120x23
Snap Ring	No
Width (mm)	23
Bearing No.	7213B
Grease lub.	3800
Flush Ground	No
Contact Angle	40 Degree
Inch - Metric	Metric
Cage Material	Steel
Product Group	B00308
Keyword String	Angular Contact
Bearing number	7213B
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Angle (?)	40 °
(Refer.)Mass(kg)	1.02
Outside Diameter	4.724 Inch 120 Millimeter
Manufacturer URL	http://www.koyousa.com
Long Description	65MM Bore; 120MM Outside Diameter; 23MM Width; Open; No Flush Ground; Ball Bearing; Single Row of Balls; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; C0-Medium; Steel Cage; 40 Degree; 1 (Single)
Weight / Kilogram	0
Manufacturer Name	KOYO
Number of Bearings	1 (Single)
Internal Clearance	C0-Medium
Bore Diameter (mm)	65

Outer Diameter (mm)	120
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.28
Number of Rows of Balls	Single Row
(Grease) Lubrication Speed	4800 r/min
Maximum Capacity / Filling Slot	No