



**Bearing No. 7213BDB**

D	120 mm
a	27.4 mm
C	23 mm
B	23 mm
d	65 mm
r1	1 mm
2B	46 mm
Width	23 mm
r min.	1.5 mm
Weight	1.02 Kg
ra max.	1 mm
r1 min.	1 mm
da min.	70 mm
Da max.	114.6 mm
ra (max)	1.5 mm
da1 (min)	74 mm
Bore Size	65 mm
Enclosure	Open
Bore Type	Cylindrical Bore
ra1 (max)	1 mm
Size (mm)	65x120x23
da2 (min)	70 mm
Da2 (max)	114.6 mm
Da1 (max)	111 mm
Width (mm)	23
Configuration	Duplex
Bearing number	7213BDB
Angle (?)	40 °
Outside Diameter	120 mm
Static Load Rating	109,000 N

Bore Diameter (mm)	65
Dynamic Load Rating	107,000 N
Outer Diameter (mm)	120
Limiting Speed - Oil	4,600 rpm
Fillet Radius/Chamfer	1.5 mm
Limiting Speed - Grease	3,400 rpm
(Grease) Lubrication Speed	3400 r/min
Basic dynamic load rating (C)	107 kN
Basic static load rating (C0)	109 kN