



**Bearing No. 7313CDF**

|                    |                  |
|--------------------|------------------|
| C                  | 33 mm            |
| d                  | 65 mm            |
| B                  | 33 mm            |
| D                  | 140 mm           |
| r1                 | 1.1 mm           |
| 2B                 | 66 mm            |
| a -                | 4.7 mm           |
| Width              | 33 mm            |
| r min.             | 2.1 mm           |
| Weight             | 2.22 Kg          |
| ra max.            | 1 mm             |
| r1 min.            | 1.1 mm           |
| da min.            | 77 mm            |
| Da max.            | 133 mm           |
| ra (max)           | 2 mm             |
| da1 (min)          | 77 mm            |
| Bore Size          | 65 mm            |
| Enclosure          | Open             |
| Bore Type          | Cylindrical Bore |
| ra1 (max)          | 1 mm             |
| Size (mm)          | 65x140x33        |
| da2 (min)          | 77 mm            |
| Da2 (max)          | 133 mm           |
| Da1 (max)          | 128 mm           |
| Width (mm)         | 33               |
| Configuration      | Duplex           |
| Bearing number     | 7313CDF          |
| Angle (?)          | 15 °             |
| Outside Diameter   | 140 mm           |
| Static Load Rating | 162,000 N        |

|                               |            |
|-------------------------------|------------|
| Bore Diameter (mm)            | 65         |
| Dynamic Load Rating           | 183,000 N  |
| Outer Diameter (mm)           | 140        |
| Limiting Speed - Oil          | 8,800 rpm  |
| Fillet Radius/Chamfer         | 2.1 mm     |
| Limiting Speed - Grease       | 6,200 rpm  |
| (Grease) Lubrication Speed    | 6200 r/min |
| Basic dynamic load rating (C) | 183 kN     |
| Basic static load rating (C0) | 162 kN     |