



Bearing No. 7214 BEGAM

D	125 mm
d	70 mm
B	24 mm
a	53 mm
Bore	2.756 Inch 70 Millimeter
Noun	Bearing
Width	0.945 Inch 24 Millimeter
UNSPSC	31171531
Preload	Light
series:	72
Category	Angular Contact Ball Bearing
Size (mm)	125x70x24
Enclosure	Open
Snap Ring	No
Inventory	2.0
Width (mm)	24
Weight / LBS	2.619
Flush Ground	Yes
Mass bearing	1.1 kg
maximum rpm:	6300 RPM
Product Group	B00308
Inch - Metric	Metric
closure type:	Open
Contact Angle	40 Degree
Cage Material	Brass
D ₁	104.75 mm
d ₂	80.25 mm
d ₁	91.5 mm

cage material:	Brass
Keyword String	Angular Contact
overall width:	24 mm
contact angle:	40 °
fillet radius:	1.5 mm
bore diameter:	70 mm
Bearing number	7214 BEGAM
Limiting speed	6300 r/min
finish/coating:	Uncoated
Rolling Element	Ball Bearing
Precision Class	ABEC 3 ISO P6
Reference speed	6300 r/min
Long Description	70MM Bore; 125MM Outside Diameter; 24MM Width; Open; Yes Flush Ground; Ball Bearing; Single Row of Balls; ABEC 3 ISO P6; No Filling Slot; No Snap Ring
Outside Diameter	4.921 Inch 125 Millimeter
Manufacturer URL	http://www.skf.com
Weight / Kilogram	1.19
precision rating:	ABEC 3 (ISO Class 6)
outside diameter:	125 mm
outer ring width:	24 mm
Manufacturer Name	SKF
Bore Diameter (mm)	125
r _b max.	1 mm
r _a max.	1.5 mm
D _b max.	119 mm
D _a max.	116 mm
d _a min.	79 mm

Number of Bearings	1 (Single)
Internal Clearance	C0-Medium
Outer Diameter (mm)	70
internal clearance:	C0
D_a - max.	116 mm
Calculation factor A	0.0529
$r_{1,2}$ min.	1.5 mm
d_a - min.	79 mm
Minimum Buy Quantity	N/A
Mounting Arrangement	Universal
$r_{3,4}$ min.	1 mm
r_a - max.	1.5 mm
r_b - max.	1 mm
Calculation factor X	0.57
Calculation factor e	1.14
D_b - max.	119 mm
d_1 ?	91.5 mm
row type & fill slot:	Single-Row Non-Fill Slot
D_1 ?	104.75 mm
d_2 ?	80.25 mm
Harmonized Tariff Code	8482.10.50.28
Calculation factor - X	0.35
Calculation factor - e	1.14
$r_{1,2}$ - min.	1.5 mm
$r_{3,4}$ - min.	1 mm
Number of Rows of Balls	Single Row
Manufacturer Item Number	7214 BEGAM
Basic dynamic load rating C	72 kN
radial static load capacity:	60 kN
radial dynamic load	72 kN

capacity:	
Basic dynamic load rating - C	72 kN
Maximum Capacity / Filling Slot	No
Calculation factor Y_0	0.52
Calculation factor Y_2	0.93
Calculation factor Y_1	0.55
Calculation factor k_r	0.095
Fatigue load limit P_u	2.55 kN
Fatigue load limit - P_u	2.6 kN
Calculation factor - k_a	1.4
Calculation factor - k_r	0.095
Calculation factor - Y_1	
Calculation factor - Y_2	0.57
Calculation factor - Y_0	0.26
Basic static load rating C_0	60 kN
Basic static load rating - C_0	60 kN