



Bearing No. 7313 BECBP

a	60 mm
d	65 mm
D	140 mm
B	33 mm
Noun	Bearing
Bore	2.559 Inch 65 Millimeter
Width	1.299 Inch 33 Millimeter
UNSPSC	31171531
series:	73
Category	Angular Contact Ball Bearing
Enclosure	Open
Snap Ring	No
Size (mm)	140x65x33
Inventory	0.0
Width (mm)	33
Weight / LBS	4.63
maximum rpm:	6300 RPM
Flush Ground	Yes
Mass bearing	2.15 kg
Contact Angle	40 Degree
Cage Material	Polymer
closure type:	Open
Product Group	B00308
Inch - Metric	Metric
d ₁	94.15 mm
D ₁	112.85 mm
d ₂	78.45 mm

Bearing number	7313 BECBP
bore diameter:	65 mm
Other Features	Normal Axial Internal Clearance
Keyword String	Angular Contact
cage material:	Nylon
Limiting speed	6300 r/min
overall width:	33 mm
contact angle:	40 °
fillet radius:	2 mm
Reference speed	6300 r/min
finish/coating:	Uncoated
Rolling Element	Ball Bearing
Precision Class	ABEC 3 ISO P6
Long Description	65MM Bore; 140MM Outside Diameter; 33MM Width; Open; Yes Flush Ground; Ball Bearing; Single Row of Balls; ABEC 3 ISO P6; No Filling Slot; No Snap Ring
Manufacturer URL	http://www.skf.com
Outside Diameter	5.512 Inch 140 Millimeter
precision rating:	Not Rated
outer ring width:	33 mm
Manufacturer Name	SKF
outside diameter:	140 mm
Weight / Kilogram	2.1
r _b max.	1 mm
Bore Diameter (mm)	140
D _a max.	128 mm
D _b max.	133 mm
r _a max.	2 mm

d_a min.	77 mm
Internal Clearance	CB
Number of Bearings	1 (Single)
internal clearance:	C0
Outer Diameter (mm)	65
Calculation factor A	0.112
d_a - min.	77 mm
r_a - max.	2 mm
D_b - max.	133 mm
Mounting Arrangement	Universal
Minimum Buy Quantity	N/A
$r_{1,2}$ min.	2.1 mm
D_a - max.	128 mm
$r_{3,4}$ min.	1.1 mm
Calculation factor X	0.57
Calculation factor e	1.14
r_b - max.	1 mm
D_1 ?	112.85 mm
d_2 ?	78.45 mm
d_1 ?	94.15 mm
row type & fill slot:	Single-Row Non-Fill Slot
Calculation factor - X	0.35
Calculation factor - e	1.14
$r_{1,2}$ - min.	2.1 mm
Harmonized Tariff Code	8482.10.50.28
$r_{3,4}$ - min.	1.1 mm
Number of Rows of Balls	Single Row
Manufacturer Item Number	7313 BECBP
Basic dynamic load rating C	116 kN
radial static load capacity:	86.5 kN

Basic dynamic load rating - C	116 kN
radial dynamic load capacity:	116 kN
Maximum Capacity / Filling Slot	No
Calculation factor k_r	0.1
Calculation factor Y_1	0.55
Calculation factor Y_2	0.93
Calculation factor Y_0	0.52
Fatigue load limit P_u	3.65 kN
Calculation factor - Y_2	0.57
Calculation factor - k_r	0.1
Calculation factor - Y_0	0.26
Calculation factor - Y_1	
Fatigue load limit - P_u	3.6 kN
Calculation factor - k_a	1.6
Basic static load rating C_0	86.5 kN
Basic static load rating - C_0	86.5 kN