



Bearing No. 53178/53375

| | |
|---------------------------------|--------------------|
| R | 2 mm |
| d | 44,45 mm |
| D | 95,25 mm |
| T | 30,958 mm |
| B | 28,301 mm |
| C | 20,638 mm |
| r | 0,8 mm |
| Da | 89 mm |
| Ab | 2,2 mm |
| Aa | 5,7 mm |
| Db | 81 mm |
| da | 52,5 mm |
| db | 60 mm |
| a - | 0,3 mm |
| Weight | 0,95 Kg |
| Size (mm) | 44.45x95.25x30.958 |
| Width (mm) | 30,958 |
| Factor (K) | 0,79 |
| Factor (G1) | 26,7 |
| Factor (Cg) | 0,0242 |
| Factor (G2) | 9,6 |
| Bearing number | 53178/53375 |
| Bore Diameter (mm) | 44,45 |
| Outer Diameter (mm) | 95,25 |
| Calculation factor (e) | 0,74 |
| Basic static load rating (C0) | 104 kN |
| Basic dynamic load rating (C1) | 92,8 kN |
| Basic dynamic load rating (C90) | 24 |

| | |
|----------------------------------|------|
| Basic dynamic load rating (Ca90) | 30,5 |
|----------------------------------|------|