



**Bearing No. 7215CDB**

C	25 mm
d	75 mm
B	25 mm
D	130 mm
r1	1 mm
2B	50 mm
a -	0.7 mm
Width	25 mm
r min.	1.5 mm
Weight	1.23 Kg
ra max.	1 mm
r1 min.	1 mm
da min.	84 mm
Da max.	124.6 mm
ra (max)	1.5 mm
da1 (min)	84 mm
Bore Size	75 mm
Enclosure	Open
Bore Type	Cylindrical Bore
ra1 (max)	1 mm
Size (mm)	75x130x25
da2 (min)	84 mm
Da2 (max)	124.6 mm
Da1 (max)	121 mm
Width (mm)	25
Configuration	Duplex
Bearing number	7215CDB
Angle (?)	15 °
Outside Diameter	130 mm
Static Load Rating	141,000 N

Bore Diameter (mm)	75
Dynamic Load Rating	135,000 N
Outer Diameter (mm)	130
Limiting Speed - Oil	8,800 rpm
Fillet Radius/Chamfer	1.5 mm
Limiting Speed - Grease	6,200 rpm
(Grease) Lubrication Speed	6200 r/min
Basic dynamic load rating (C)	135 kN
Basic static load rating (C0)	141 kN