



Bearing No. 6217

r	2
d	85 mm
D	150 mm
B	28 mm
C	28 mm
fo	14.5
D_	150
B_	28
ra	2
Z_	10
C0	62
DI_	96.862
SRE	10.68
D_a	141
DE_	138.138
SRI	10.68
DA_	20.638
SREN	-0.04
Noun	Bearing
SRIN	-0.04
bomp	0
SRIX	0.04
yobi	6217
mass	1.76
SDM_	117.5
KBRG	6101
SREX	0.04
SBRG	2
Bore	3.346 Inch 85 Millimeter

LangID	1
Weight	1,76 Kg
r min.	2 mm
ALPHA_	0
C_conv	84000
da min	94
UNSPSC	31171504
da max	102 mm
Oil rpm	5000
GRS rpm	4300
ra max.	2 mm
hidYobi	6217
Da max.	141 mm
da min.	94 mm
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Inventory	0.0
Snap Ring	No
Enclosure	Open
Size (mm)	85x150x28
Prod_Type3	DGBB_SR_OT
bore type:	Round
Width (mm)	28
Weight / LBS	1.77
Inch - Metric	Metric
closure type:	Open
Product Group	B00308
Cage Material	Steel
Keyword String	Ball
overall width:	28 mm
Bearing number	6217
bore diameter:	85 mm

Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Outside Diameter	5.906 Inch 150 Millimeter
Long Description	85MM Bore; 150MM Outside Diameter; 28MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Manufacturer URL	http://www.nskamericas.com
Outer Race Width	1.102 Inch 28 Millimeter
Weight / Kilogram	0.8
Manufacturer Name	NSK
outside diameter:	150 mm
Internal Clearance	C0-Medium
Bore Diameter (mm)	85
Outer Diameter (mm)	150
internal clearance:	Normal Clearance
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
(Oil) Lubrication Speed	5 000 r/min
manufacturer upc number:	029176015632
Manufacturer Item Number	6217
Internal Special Features	No
(Grease) Lubrication Speed	4 300 r/min
Basic dynamic load rating (C)	84 kN
Basic static load rating	62 kN

(C0)	
Maximum Capacity / Filling Slot	No