



Bearing No. 46344

| | |
|-------------|-------------|
| e | 0.35 |
| d | 220 mm |
| D | 370 mm |
| T | 120 mm |
| C | 107 mm |
| Y0 | 1.91 |
| Y3 | 2.90 |
| Cu | 101 |
| Y2 | 1.95 |
| Cr | 1260 |
| C0r | 1810 |
| r(min) | 5 |
| Weight | 49,1 Kg |
| Da min | 346 mm |
| r min. | 5 mm |
| r1(min) | 1.5 |
| Sa(min) | 6.5 |
| ra(max) | 4 |
| da(min) | 242 |
| rb(max) | 1.5 |
| Da(min) | 361.5 |
| rb max. | 1,5 mm |
| ra max. | 4 mm |
| da min. | 242 mm |
| r1 min. | 1,5 mm |
| Oil lub. | 930 |
| Size (mm) | 220x370x120 |
| Width (mm) | 120 |
| Bearing No. | 46344 |
| Grease lub. | 700 |

| | |
|-------------------------------|-----------|
| Bearing number | 46344 |
| (Refer.)Mass(kg) | 49.1 |
| Bore Diameter (mm) | 220 |
| Outer Diameter (mm) | 370 |
| Calculation factor (e) | 0,35 |
| Calculation factor (Y0) | 1,91 |
| (Oil) Lubrication Speed | 930 r/min |
| (Grease) Lubrication Speed | 700 r/min |
| Basic static load rating (C0) | 1810 kN |
| Basic dynamic load rating (C) | 1070 kN |