



### Bearing No. 7216B

a	59.2 mm
d	80 mm
D	140 mm
B	26 mm
C	26 mm
Cr	101
f0	-
Cu	3.80
C0r	69.3
Noun	Bearing
Bore	3.15 Inch   80 Millimeter
Width	1.024 Inch   26 Millimeter
a(mm)	59.2
UNSPSC	31171531
r(min)	2
r min.	2 mm
Weight	1.50 Kg
da min.	90 mm
ra(max)	2
ra max.	2 mm
r1 min.	1 mm
Da max.	130 mm
da(min)	90
r1(min)	1
Da(max)	130
Category	Angular Contact Ball Bearing
Oil lub.	4300
Snap Ring	No
Enclosure	Open

Size (mm)	80x140x26
Inventory	0.0
Width (mm)	26
Bearing No.	7216B
Grease lub.	3200
Flush Ground	No
Contact Angle	40 Degree
Inch - Metric	Metric
Cage Material	Steel
Product Group	B00308
Keyword String	Angular Contact
Bearing number	7216B
Precision Class	ABEC 1   ISO P0
Rolling Element	Ball Bearing
Angle (?)	40 °
(Refer.)Mass(kg)	1.50
Outside Diameter	5.512 Inch   140 Millimeter
Manufacturer URL	<a href="http://www.koyousa.com">http://www.koyousa.com</a>
Long Description	80MM Bore; 140MM Outside Diameter; 26MM Width; Open; No Flush Ground; Ball Bearing; Single Row of Balls; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; C0-Medium; Steel Cage; 40 Degree; 1 (Single)
Weight / Kilogram	0
Manufacturer Name	KOYO
Number of Bearings	1 (Single)
Internal Clearance	C0-Medium
Bore Diameter (mm)	80
Outer Diameter (mm)	140

Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.28
Number of Rows of Balls	Single Row
(Grease) Lubrication Speed	4000 r/min
Maximum Capacity / Filling Slot	No