



Bearing No. 6217DDU

r	2
d	85 mm
D	150 mm
B	28 mm
C	28 mm
D_	150
C0	62
Z_	10
ra	2
fo	14.5
B_	28
DI_	96.862
SRI	10.68
SRE	10.68
DE_	138.138
DA_	20.638
D_a	141
KBRG	6161
SBRG	2
SRIN	-0.04
bomp	0
SREX	0.04
yobi	6217DDU
SRIX	0.04
mass	1.76
SDM_	117.5
SREN	-0.04
Bore	3.346 Inch   85 Millimeter
Noun	Bearing

LangID	1
UNSPSC	31171504
da min	94
r min.	2 mm
Weight	1,76 Kg
ALPHA_	0
C_conv	84000
da max	102 mm
GRS rpm	2800
Da max.	141 mm
ra max.	2 mm
da min.	94 mm
hidYobi	6217DDU
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Size (mm)	85x150x28
Enclosure	2 Seals
Snap Ring	No
Inventory	0.0
Width (mm)	28
Prod_Type3	DGBB_SR_DD
Weight / LBS	3.8808
Inch - Metric	Metric
Product Group	B00308
Cage Material	Steel
Bearing number	6217DDU
Keyword String	Ball
Other Features	Deep Groove   Rubber Seal
Enclosure Type	Contact Seal
Precision Class	ABEC 1   ISO P0
Rolling Element	Ball Bearing
Inner Race Width	0 Inch   0 Millimeter

Outside Diameter	5.906 Inch   150 Millimeter
Long Description	85MM Bore; 150MM Outside Diameter; 28MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage;
Manufacturer URL	<a href="http://www.nskamericas.com">http://www.nskamericas.com</a>
Outer Race Width	1.102 Inch   28 Millimeter
Manufacturer Name	NSK
Weight / Kilogram	1.9
Internal Clearance	C0-Medium
Bore Diameter (mm)	85
Outer Diameter (mm)	150
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6217DDU
Internal Special Features	No
(Grease) Lubrication Speed	2 800 r/min
Basic static load rating (C0)	62 kN
Basic dynamic load rating (C)	84 kN
Maximum Capacity / Filling Slot	No