



Bearing No. 6217LLB

C	28 mm
d	85 mm
D	150 mm
B	28 mm
Bore	3.346 Inch 85 Millimeter
Noun	Bearing
Weight	1,79 Kg
r min.	2 mm
da max	103 mm
UNSPSC	31171504
da min.	94 mm
Da max.	141 mm
ra max.	2 mm
Category	Single Row Ball Bearing
Size (mm)	85x150x28
Snap Ring	No
Inventory	0.0
Enclosure	2 Seals
Width (mm)	28
bore type:	Round
Weight / LBS	3.96832
Inch - Metric	Metric
closure type:	Double Sealed
Product Group	B00308
Cage Material	Steel
bore diameter:	85 mm
Keyword String	Ball
overall width:	28 mm
cage material:	Steel

fillet radius:	2 mm
Other Features	Deep Groove Non-Friction Nitrile Rubber Seal Shell Alvania Prelubricated
Bearing number	6217LLB
Enclosure Type	Non-Contact Seal
finish/coating:	Uncoated
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
Manufacturer URL	http://www.ntnamerica.com
Inner Race Width	0 Inch 0 Millimeter
Long Description	85MM Bore; 150MM Outside Diameter; 28MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage;
Outer Race Width	1.102 Inch 28 Millimeter
Outside Diameter	5.906 Inch 150 Millimeter
Manufacturer Name	NTN
bearing material:	High Carbon Chrome Steel
precision rating:	ISO Class 0
Weight / Kilogram	0
inner ring width:	28 mm
outer ring width:	28 mm
outside diameter:	150 mm
Bore Diameter (mm)	85
Internal Clearance	C0-Medium

snap ring included:	Without Snap Ring
Outer Diameter (mm)	150
internal clearance:	CN
Minimum Buy Quantity	N/A
static load capacity:	64000 N
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm (grease):	4200 rpm
Harmonized Tariff Code	8482.10.50.68
dynamic load capacity:	83500 N
Internal Special Features	No
(Grease) Lubrication Speed	4 200 r/min
manufacturer product page:	Click here
operating temperature range:	-40 to 120 °C
Basic static load rating (C0)	64 kN
Basic dynamic load rating (C)	83,5 kN
Maximum Capacity / Filling Slot	No