



### Bearing No. 6217VV

D	150 mm
d	85 mm
B	28 mm
C	28 mm
r	2
Z_	10
B_	28
D_	150
ra	2
C0	62
fo	14.5
DI_	96.862
SRI	10.68
D_a	141
DE_	138.138
DA_	20.638
SRE	10.68
SRIN	-0.04
SBRG	2
yobi	6217VV
SDM_	117.5
SREX	0.04
KBRG	6151
bomp	0
mass	1.76
Bore	3.346 Inch   85 Millimeter
SRIX	0.04
SREN	-0.04
Noun	Bearing

ALPHA_	0
da min	94
LangID	1
r min.	2 mm
UNSPSC	31171504
da max	102 mm
C_conv	84000
Weight	1,76 Kg
ra max.	2 mm
hidYobi	6217VV
GRS rpm	4300
da min.	94 mm
Da max.	141 mm
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Snap Ring	No
Size (mm)	85x150x28
Enclosure	2 Seals
Inventory	0.0
Width (mm)	28
Prod_Type3	DGBB_SR_VV
Weight / LBS	1.77
Cage Material	Steel
Product Group	B00308
Inch - Metric	Metric
Bearing number	6217VV
Keyword String	Ball
Enclosure Type	Non-Contact Seal
Precision Class	ABEC 1   ISO P0
Rolling Element	Ball Bearing
Outer Race Width	1.102 Inch   28 Millimeter
Outside Diameter	5.906 Inch   150

	Millimeter
Long Description	85MM Bore; 150MM Outside Diameter; 28MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Manufacturer URL	<a href="http://www.nskamericas.com">http://www.nskamericas.com</a>
Weight / Kilogram	1.77
Manufacturer Name	NSK
Internal Clearance	C0-Medium
Bore Diameter (mm)	85
Outer Diameter (mm)	150
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6217VV
Internal Special Features	No
(Grease) Lubrication Speed	4 300 r/min
Basic static load rating (C0)	62 kN
Basic dynamic load rating (C)	84 kN
Maximum Capacity / Filling Slot	No