



Bearing No. 46780/46720

e	0.38
d	158,75 mm
D	225,425 mm
T	41,275 mm
B	39,688 mm
C	33,338 mm
a	44,3 mm
Da	209 mm
B_	39.688
Db	218 mm
da	176 mm
Y0	0.86
db	169 mm
C0	540
D_	225.425
Z_	44
C_	33.338
Y1	1.6
DE_	206.519
SLR	29
D_a	209
DI_	185.731
DA1	11.332
DA2	10.573
CUP	1.66
DA_	10.953
D_b	218
RAr	432.852
SDM_	196.508
KBRG	3161

yobi	46780/46720
CONE	3.69
ALP21	28
ALP22	40
ALP23	0
BETA_	0
BET21	1
BET23	0
BET22	30
r min.	3,5 mm
LangID	1
Weight	5,35 Kg
ALPHA_	14.333
r1 min.	3,3 mm
ra max.	3,5 mm
Oil rpm	1900
outer r	3.3
hidYobi	46780/46720
GRS rpm	1400
inner r	3.5
hidTable	ecat_NSTPRI
inner ra	3.5
outer rb	3.3
ra1 max.	3,3 mm
Size (mm)	158.75x225.425x41.275
SHOG_yobi	46780/46720
Prod_Type3	TRBSR_ID_A
Width (mm)	41,275
Bearing number	46780/46720
Bore Diameter (mm)	158,75
Outer Diameter (mm)	225,425
Calculation factor (e)	0,38

(Oil) Lubrication Speed	1900 r/min
Calculation factor (Y0)	0,86
(Grease) Lubrication Speed	1400 r/min
Basic static load rating (C0)	540 kN
Basic dynamic load rating (C)	240 kN