



Bearing No. 6217ZZ

D	150 mm
d	85 mm
B	28 mm
C	28 mm
r	2
ra	2
Z_	10
B_	28
D_	150
fo	14.5
C0	62
D_a	141
DE_	138.138
DI_	96.862
SRE	10.68
SRI	10.68
DA_	20.638
SRIX	0.04
bomp	0
SRIN	-0.04
Noun	Bearing
Bore	3.346 Inch 85 Millimeter
SREN	-0.04
SREX	0.04
mass	1.76
KBRG	6141
SBRG	2
yobi	6217ZZ
SDM_	117.5

Weight	1,76 Kg
LangID	1
r min.	2 mm
ALPHA_	0
UNSPSC	31171504
da min	94
C_conv	84000
da max	102 mm
da min.	94 mm
GRS rpm	4300
hidYobi	6217ZZ
ra max.	2 mm
Da max.	141 mm
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Enclosure	2 Metal Shields
Size (mm)	85x150x28
Inventory	0.0
Snap Ring	No
Width (mm)	28
Prod_Type3	DGBB_SR_ZZ
Weight / LBS	1.77
Product Group	B00308
Inch - Metric	Metric
Cage Material	Steel
Bearing number	6217ZZ
Keyword String	Ball
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
Manufacturer URL	http://www.nskamericas.com
Outside Diameter	5.906 Inch 150 Millimeter

Outer Race Width	1.102 Inch 28 Millimeter
Long Description	85MM Bore; 150MM Outside Diameter; 28MM Outer Race Diameter; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Manufacturer Name	NSK
Weight / Kilogram	1.77
Internal Clearance	C0-Medium
Bore Diameter (mm)	85
Outer Diameter (mm)	150
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6217ZZ
Internal Special Features	No
(Grease) Lubrication Speed	4 300 r/min
Basic static load rating (C0)	62 kN
Basic dynamic load rating (C)	84 kN
Maximum Capacity / Filling Slot	No