



Bearing No. NNU 4984 B/SPW33

S	5,5 mm
K	9 mm
d	420 mm
D	560 mm
B	140 mm
C	140 mm
b	16,7 mm
F	466 mm
dh	– mm
D1	510,5 mm
s max.	5.5 mm
Weight	91 Kg
db min	471 mm
da max	461 mm
Da max.	544 mm
da min.	435 mm
ra max.	3 mm
r4 min.	2 mm
r3 min.	2 mm
r1 min.	4 mm
r2 min.	4 mm
Size (mm)	420x560x140
Width (mm)	140
Mass bearing	91 kg
D ₁	510.5 mm
Bearing number	NNU 4984 B/SPW33
d _a min.	435 mm
r _a max.	3 mm
D _a max.	544 mm
d _b min.	471 mm

d_a max.	461 mm
Bore Diameter (mm)	420
Outer Diameter (mm)	560
$r_{1,2}$ min.	4 mm
(Oil) Lubrication Speed	1 400 r/min
(Grease) Lubrication Speed	1 200 r/min
Basic dynamic load rating C	1510 kN
Basic dynamic load rating (C)	1 510 kN
Basic static load rating (C ₀)	4 000 kN
Fatigue load limit P_u	335 kN
Basic static load rating C ₀	4000 kN
Attainable speed for grease lubrication	1200 r/min
Attainable speed for oil-air lubrication	1400 r/min