



Bearing No. NNU 4984 BK/SPW33

s	5.5 mm
d	420 mm
D	560 mm
B	140 mm
F	466 mm
b	16.7 mm
K	9 mm
s max.	5.5 mm
Size (mm)	420x560x140
Width (mm)	140
Mass bearing	91 kg
D ₁	510.5 mm
D ₁	510.5 mm
Bearing number	NNU 4984 BK/SPW33
D _a max.	544 mm
r _a max.	3 mm
d _a max.	461 mm
d _a min.	435 mm
Bore Diameter (mm)	420
Outer Diameter (mm)	560
r _{3,4} min.	2 mm
d _a - min.	435 mm
d _a - max.	461 mm
D _a - max.	544 mm
r _a - max.	3 mm
r _{1,2} min.	4 mm
r _{3,4} - min.	2 mm
r _{1,2} - min.	4 mm
Basic dynamic load rating C	1510 kN

Basic dynamic load rating - C	1510 kN
Fatigue load limit P_u	335 kN
Limiting speed for oil lubrication	1400 r/min
Fatigue load limit - P_u	335 kN
Limiting speed for grease lubrication	1200 r/min
Basic static load rating C_0	4000 kN
Attainable speed for grease lubrication	1200 r/min
Basic static load rating - C_0	4000 kN
Attainable speed for oil-air lubrication	1400 r/min