



Bearing No. NNU 4992 BK/SPW33

s	3.2 mm
d	460 mm
D	620 mm
B	160 mm
F	510 mm
b	16.7 mm
K	9 mm
s max.	3.2 mm
Size (mm)	460x620x160
Width (mm)	160
Mass bearing	130 kg
D <sub>1</sub>	567 mm
D <sub>1</sub>	567 mm
Bearing number	NNU 4992 BK/SPW33
D <sub>a</sub> max.	605 mm
r <sub>a</sub> max.	3 mm
d <sub>a</sub> max.	504 mm
d <sub>a</sub> min.	475 mm
Bore Diameter (mm)	460
Outer Diameter (mm)	620
r <sub>3,4</sub> min.	2 mm
d <sub>a</sub> - min.	475 mm
d <sub>a</sub> - max.	504 mm
D <sub>a</sub> - max.	605 mm
r <sub>a</sub> - max.	3 mm
r <sub>1,2</sub> min.	4 mm
r <sub>3,4</sub> - min.	2 mm
r <sub>1,2</sub> - min.	4 mm
Basic dynamic load rating C	2090 kN

Basic dynamic load rating - C	2090 kN
Fatigue load limit $P_u$	465 kN
Limiting speed for oil lubrication	1200 r/min
Fatigue load limit - $P_u$	465 kN
Limiting speed for grease lubrication	1000 r/min
Basic static load rating $C_0$	5500 kN
Attainable speed for grease lubrication	1000 r/min
Basic static load rating - $C_0$	5500 kN
Attainable speed for oil-air lubrication	1200 r/min