



Bearing No. 7310B

| | |
|-----------|---------------------------------|
| a | 47.9 mm |
| d | 50 mm |
| D | 110 mm |
| B | 27 mm |
| C | 27 mm |
| Cr | 85.3 |
| f0 | - |
| Cu | 3.15 |
| C0r | 48.3 |
| Noun | Bearing |
| Bore | 1.969 Inch 50 Millimeter |
| Width | 1.063 Inch 27 Millimeter |
| a(mm) | 47.9 |
| UNSPSC | 31171531 |
| r(min) | 2 |
| r min. | 2 mm |
| Weight | 1.14 Kg |
| da min. | 60 mm |
| ra(max) | 2 |
| ra max. | 2 mm |
| r1 min. | 1 mm |
| Da max. | 100 mm |
| da(min) | 60 |
| r1(min) | 1 |
| Da(max) | 100 |
| Category | Angular Contact Ball Bearing |
| Oil lub. | 5800 |
| Snap Ring | No |

| | |
|--------------------|--|
| Enclosure | Open |
| Size (mm) | 50x110x27 |
| Inventory | 0.0 |
| Width (mm) | 27 |
| Bearing No. | 7310B |
| Grease lub. | 4400 |
| Flush Ground | No |
| Contact Angle | 40 Degree |
| Inch - Metric | Metric |
| Cage Material | Steel |
| Product Group | B00308 |
| Keyword String | Angular Contact |
| Bearing number | 7310B |
| Precision Class | ABEC 1 ISO P0 |
| Rolling Element | Ball Bearing |
| Angle (?) | 40 ° |
| (Refer.)Mass(kg) | 1.14 |
| Outside Diameter | 4.331 Inch 110 Millimeter |
| Manufacturer URL | http://www.koyousa.com |
| Long Description | 50MM Bore; 110MM Outside Diameter; 27MM Width; Open; No Flush Ground; Ball Bearing; Single Row of Balls; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; C0-Medium; Steel Cage; 40 Degree; 1 (Single) |
| Weight / Kilogram | 0 |
| Manufacturer Name | KOYO |
| Number of Bearings | 1 (Single) |
| Internal Clearance | C0-Medium |
| Bore Diameter (mm) | 50 |
| | |

| | |
|---------------------------------|---------------|
| Outer Diameter (mm) | 110 |
| Minimum Buy Quantity | N/A |
| Harmonized Tariff Code | 8482.10.50.28 |
| Number of Rows of Balls | Single Row |
| (Grease) Lubrication Speed | 5500 r/min |
| Maximum Capacity / Filling Slot | No |