



Bearing No. NNU 4968 BK/SPW33

| | |
|---------------------|-------------------|
| S | 5,5 mm |
| K | 9 mm |
| d | 340 mm |
| D | 460 mm |
| B | 118 mm |
| C | 118 mm |
| b | 16,7 mm |
| F | 379 mm |
| dh | – mm |
| D1 | 419 mm |
| s max. | 5.5 mm |
| Weight | 53 Kg |
| db min | 383 mm |
| da max | 375 mm |
| Da max. | 447 mm |
| da min. | 353 mm |
| ra max. | 2,5 mm |
| r4 min. | 1,5 mm |
| r3 min. | 1,5 mm |
| r1 min. | 3 mm |
| r2 min. | 3 mm |
| Size (mm) | 340x460x118 |
| Width (mm) | 118 |
| Mass bearing | 56 kg |
| D ₁ | 419 mm |
| Bearing number | NNU 4968 BK/SPW33 |
| Bore Diameter (mm) | 340 |
| r _a max. | 2.5 mm |
| D _a max. | 447 mm |
| d _a max. | 375 mm |

| | |
|--|-------------|
| d_a min. | 353 mm |
| Outer Diameter (mm) | 460 |
| $r_{3,4}$ min. | 1.5 mm |
| $r_{1,2}$ min. | 3 mm |
| (Oil) Lubrication Speed | 1 700 r/min |
| (Grease) Lubrication Speed | 1 500 r/min |
| Basic dynamic load rating C | 1100 kN |
| Basic dynamic load rating (C) | 1 100 kN |
| Basic static load rating (C0) | 2 650 kN |
| Fatigue load limit P_u | 245 kN |
| Basic static load rating C_0 | 2650 kN |
| Attainable speed for grease lubrication | 1500 r/min |
| Attainable speed for oil-air lubrication | 1700 r/min |