



Bearing No. 2310

r	2
d	50 mm
D	110 mm
B	40 mm
C	40 mm
e	0.42
Y0	1.6
X1	1
B_	40
ra	2
Y2	2.3
D_	110
Y3	1.5
C0	20.2
X0	1
da	59
X2	0.65
PCD	78.7
D_a	101
SRI	9.17
SRE	0
mass	1.58
CAng	15.753
KBRG	1354
yobi	2310
SREX	0
SRIX	0.065
SRIN	0
SREN	0
r min.	2 mm

Weight	1,58 Kg
LangID	1
GRS rpm	5000
cyl dia	17.462
Oil rpm	6300
hidYobi	2310
da min.	59 mm
Da max.	101 mm
ra max.	2 mm
hidTable	ecat_NSSAB
cyl count	12
Size (mm)	50x110x40
Prod_Type3	SABB_SA_CB
Width (mm)	40
groove inner	61.203
groove outer	99.233
Bearing number	2310
Bore Diameter (mm)	50
Outer Diameter (mm)	110
Calculation factor (e)	0,42
(Oil) Lubrication Speed	6 300 r/min
Calculation factor (Y0)	1,6
Calculation factor (Y2)	2,3
(Grease) Lubrication Speed	5 000 r/min
Basic static load rating (C0)	20,2 kN
Basic dynamic load rating (C)	65 kN