



Bearing No. NNU 49/600 B/SPW33X

S	5,5 mm
K	12 mm
d	600 mm
D	800 mm
B	200 mm
C	200 mm
b	22,3 mm
F	666 mm
dh	– mm
D1	733,2 mm
s max.	5.5 mm
Weight	280 Kg
db min	672 mm
da max	662 mm
Da max.	782 mm
da min.	648 mm
ra max.	4 mm
r4 min.	2,5 mm
r3 min.	2,5 mm
r1 min.	5 mm
r2 min.	5 mm
Size (mm)	600x800x200
Width (mm)	200
Mass bearing	280 kg
D <sub>1</sub>	733.2 mm
Bearing number	NNU 49/600 B/SPW33X
d <sub>a</sub> min.	648 mm
r <sub>a</sub> max.	4 mm
D <sub>a</sub> max.	782 mm
d <sub>b</sub> min.	672 mm

d <sub>a</sub> max.	662 mm
Bore Diameter (mm)	600
Outer Diameter (mm)	800
r <sub>1,2</sub> min.	5 mm
(Oil) Lubrication Speed	900 r/min
(Grease) Lubrication Speed	800 r/min
Basic dynamic load rating C	3580 kN
Basic dynamic load rating (C)	3 580 kN
Basic static load rating (C <sub>0</sub> )	10 200 kN
Fatigue load limit P <sub>u</sub>	800 kN
Basic static load rating C <sub>0</sub>	10200 kN
Attainable speed for grease lubrication	800 r/min
Attainable speed for oil-air lubrication	900 r/min