



Bearing No. NNU 49/600 BK/SPW33X

s	5.5 mm
d	600 mm
D	800 mm
B	200 mm
F	666 mm
b	22.3 mm
K	12 mm
s max.	5.5 mm
Size (mm)	600x800x200
Width (mm)	200
Mass bearing	280 kg
D_1	733.2 mm
D_1	733.2 mm
Bearing number	NNU 49/600 BK/SPW33X
D_a max.	782 mm
r_a max.	4 mm
d_a max.	662 mm
d_a min.	648 mm
Bore Diameter (mm)	600
Outer Diameter (mm)	800
$r_{3,4}$ min.	2.5 mm
d_a - min.	648 mm
d_a - max.	662 mm
D_a - max.	782 mm
r_a - max.	4 mm
$r_{1,2}$ min.	5 mm
$r_{3,4}$ - min.	2.5 mm
$r_{1,2}$ - min.	5 mm
Basic dynamic load rating C	3580 kN

Basic dynamic load rating - C	3580 kN
Fatigue load limit P_u	800 kN
Limiting speed for oil lubrication	900 r/min
Fatigue load limit - P_u	800 kN
Limiting speed for grease lubrication	800 r/min
Basic static load rating C_0	10200 kN
Attainable speed for grease lubrication	800 r/min
Basic static load rating - C_0	10200 kN
Attainable speed for oil-air lubrication	900 r/min