



Bearing No. NNU 49/670 B/SPW33X

S	6 mm
K	12 mm
d	670 mm
D	900 mm
B	230 mm
C	230 mm
b	22,3 mm
F	738 mm
dh	– mm
D1	821,2 mm
s max.	6 mm
Weight	410 Kg
db min	744 mm
da max	732 mm
Da max.	877 mm
da min.	693 mm
ra max.	5 mm
r4 min.	3 mm
r3 min.	3 mm
r1 min.	6 mm
r2 min.	6 mm
Size (mm)	670x900x230
Width (mm)	230
Mass bearing	410 kg
D ₁	821.2 mm
Bearing number	NNU 49/670 B/SPW33X
d _a min.	693 mm
r _a max.	5 mm
D _a max.	877 mm
d _b min.	744 mm

d _a max.	732 mm
Bore Diameter (mm)	670
Outer Diameter (mm)	900
r _{1,2} min.	6 mm
(Oil) Lubrication Speed	800 r/min
(Grease) Lubrication Speed	700 r/min
Basic dynamic load rating C	4950 kN
Basic dynamic load rating (C)	4 950 kN
Basic static load rating (C ₀)	13 700 kN
Fatigue load limit P _u	930 kN
Basic static load rating C ₀	13700 kN
Attainable speed for grease lubrication	700 r/min
Attainable speed for oil-air lubrication	800 r/min