



Bearing No. NNU 49/670 BK/SPW33X

s	6 mm
d	670 mm
D	900 mm
B	230 mm
F	738 mm
b	22.3 mm
K	12 mm
s max.	6 mm
Size (mm)	670x900x230
Width (mm)	230
Mass bearing	410 kg
D <sub>1</sub>	821.2 mm
D <sub>1</sub>	821.2 mm
Bearing number	NNU 49/670 BK/SPW33X
D <sub>a</sub> max.	877 mm
r <sub>a</sub> max.	5 mm
d <sub>a</sub> max.	732 mm
d <sub>a</sub> min.	693 mm
Bore Diameter (mm)	670
Outer Diameter (mm)	900
r <sub>3,4</sub> min.	3 mm
d <sub>a</sub> - min.	693 mm
d <sub>a</sub> - max.	732 mm
D <sub>a</sub> - max.	877 mm
r <sub>a</sub> - max.	5 mm
r <sub>1,2</sub> min.	6 mm
r <sub>3,4</sub> - min.	3 mm
r <sub>1,2</sub> - min.	6 mm
Basic dynamic load rating C	4950 kN

Basic dynamic load rating - C	4950 kN
Fatigue load limit $P_u$	930 kN
Limiting speed for oil lubrication	800 r/min
Fatigue load limit - $P_u$	930 kN
Limiting speed for grease lubrication	700 r/min
Basic static load rating $C_0$	13700 kN
Attainable speed for grease lubrication	700 r/min
Basic static load rating - $C_0$	13700 kN
Attainable speed for oil-air lubrication	800 r/min