



Bearing No. 7308BG

D	90,000 mm
d	40,000 mm
B	23,000 mm
C	23,000 mm
a	39 mm
Bore	1.575 Inch 40 Millimeter
Mass	0.64 kg
Noun	Bearing
Width	0.906 Inch 23 Millimeter
Da max	81.5 mm
Db max	84.5 mm
UNSPSC	31171531
ra max	1 mm
rs min	1.5 mm
da min	48.5 mm
db min	45.5 mm
r1s min	1 mm
r1a max	1 mm
series:	73B
weight:	0.641 kg
Category	Angular Contact Ball Bearing
Inventory	0.0
Enclosure	Open
Snap Ring	No
Size (mm)	40x90x23
Nlim (oil)	9,900 rpm
bore type:	Round
Width (mm)	23,000

Flush Ground	Yes
Weight / LBS	1.417
maximum rpm:	9900 rpm
Cage Material	Steel
Contact Angle	40 Degree
Product Group	B00308
Inch - Metric	Metric
Nlim (grease)	7,400 rpm
closure type:	Open
bore diameter:	40 mm
cage material:	Steel
Keyword String	Angular Contact
contact angle:	40 °
fillet radius:	1.5 mm
overall width:	23 mm
Bearing number	7308BG
Dynamic load, C	45 kN
finish/coating:	Uncoated
Precision Class	ABEC 1 ISO P0
Static load, C0	30.5 kN
Rolling Element	Ball Bearing
Long Description	40MM Bore; 90MM Outside Diameter; 23MM Width; Open; Yes Flush Ground; Ball Bearing; Single Row of Balls; ABEC 1 ISO P0; No Filling Slot; No Snap Ring
Manufacturer URL	http://www.ntnamerica.com
Outside Diameter	3.543 Inch 90 Millimeter
Contact angle ?	40 °
Manufacturer Name	NTN

bearing material:	High Carbon Chrome Steel
precision rating:	ISO Class 0
outer ring width:	23 mm
Weight / Kilogram	0.641
outside diameter:	90 mm
Number of Bearings	1 (Single)
Bore Diameter (mm)	40,000
Internal Clearance	C0-Medium
Outer Diameter (mm)	90,000
snap ring included:	Without Snap Ring
internal clearance:	C0
Minimum Buy Quantity	N/A
Mounting Arrangement	Universal
row type & fill slot:	Single-Row Non-Fill Slot
Fatigue limit load, Cu	1.39 kN
Harmonized Tariff Code	8482.10.50.28
Radial clearance class	CN
Number of Rows of Balls	Single Row
Manufacturer Item Number	7308BG
manufacturer product page:	Click here
operating temperature range:	-40 to 120 °C
radial static load capacity:	30500 N
radial dynamic load capacity:	45000 N
Min operating temperature, Tmin	-40 °C
Maximum Capacity / Filling Slot	No
Max operating temperature, Tmax	120 °C

