



Bearing No. 6219VV

D	170 mm
d	95 mm
B	32 mm
C	32 mm
r	2.1
Z_	10
B_	32
D_	170
ra	2
C0	82
fo	14.4
DI_	108.688
SRI	12.32
D_a	159
DE_	156.312
DA_	23.812
SRE	12.32
SRIN	-0.04
SBRG	2
yobi	6219VV
SDM_	132.5
SREX	0.04
KBRG	6151
bomp	0
mass	2.64
Bore	3.74 Inch 95 Millimeter
SRIX	0.04
SREN	-0.04
Noun	Bearing
ALPHA_	0

da min	106
LangID	1
r min.	2,1 mm
UNSPSC	31171504
da max	114 mm
C_conv	109000
Weight	2,64 Kg
ra max.	2 mm
hidYobi	6219VV
GRS rpm	3800
da min.	106 mm
Da max.	159 mm
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Snap Ring	No
Size (mm)	95x170x32
Enclosure	2 Seals
Inventory	0.0
Width (mm)	32
Prod_Type3	DGBB_SR_VV
Weight / LBS	2.64
Cage Material	Steel
Product Group	B00308
Inch - Metric	Metric
Bearing number	6219VV
Keyword String	Ball
Enclosure Type	Non-Contact Seal
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Outer Race Width	1.26 Inch 32 Millimeter
Outside Diameter	6.693 Inch 170 Millimeter
Long Description	95MM Bore; 170MM

	Outside Diameter; 32MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Manufacturer URL	http://www.nskamericas.com
Weight / Kilogram	2.7
Manufacturer Name	NSK
Internal Clearance	C0-Medium
Bore Diameter (mm)	95
Outer Diameter (mm)	170
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6219VV
Internal Special Features	No
(Grease) Lubrication Speed	3 800 r/min
Basic static load rating (C0)	82 kN
Basic dynamic load rating (C)	109 kN
Maximum Capacity / Filling Slot	No