



Bearing No. 6219ZZ

D	170 mm
d	95 mm
B	32 mm
C	32 mm
rn	0,5 mm
Bore	3.74 Inch 95 Millimeter
Noun	Bearing
da max	116 mm
UNSPSC	31171504
Weight	2,62 Kg
r min.	2,1 mm
ra max.	2 mm
da min.	106 mm
Da max.	159 mm
Category	Single Row Ball Bearing
Size (mm)	95x170x32
Snap Ring	No
Inventory	0.0
Enclosure	2 Metal Shields
Width (mm)	32
bore type:	Round
Weight / LBS	6.17294
Inch - Metric	Metric
closure type:	Double Shielded
Product Group	B00308
Cage Material	Steel
bore diameter:	95 mm
Keyword String	Ball
overall width:	32 mm
cage material:	Steel

fillet radius:	2.1 mm
Other Features	Deep Groove Shell Alvania Prelubricated
Bearing number	6219ZZ
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
finish/coating:	Uncoated
Long Description	95MM Bore; 170MM Outside Diameter; 32MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Ste
Manufacturer URL	http://www.ntnamerica.com
Outside Diameter	6.693 Inch 170 Millimeter
Outer Race Width	1.26 Inch 32 Millimeter
Inner Race Width	0 Inch 0 Millimeter
precision rating:	ISO Class 0
outer ring width:	32 mm
inner ring width:	32 mm
Weight / Kilogram	0
bearing material:	High Carbon Chrome Steel
Manufacturer Name	NTN
outside diameter:	170 mm
Bore Diameter (mm)	95
Internal Clearance	C0-Medium
snap ring included:	Without Snap Ring
Outer Diameter (mm)	170
internal clearance:	CN

Minimum Buy Quantity	N/A
static load capacity:	82000 N
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm (grease):	3700 rpm
Harmonized Tariff Code	8482.10.50.68
dynamic load capacity:	109000 N
Internal Special Features	No
(Grease) Lubrication Speed	3 700 r/min
manufacturer product page:	Click here
operating temperature range:	-40 to 120 °C
Basic static load rating (C0)	82 kN
Basic dynamic load rating (C)	109 kN
Maximum Capacity / Filling Slot	No