



Bearing No. NJ2213-E-TVP2 + HJ2213-E

m	1,46 kg / Weight
F	78,5 mm
E	108,5 mm
d	65 mm
D	120 mm
B	31 mm
s	1,9 mm / Axial displacement facility from central position
Size (mm)	65x120x31
Width (mm)	31
$C_r$	177000 N / Dynamic load rating (radial)
$m_1$	0,13 kg
$B_2$	10,5 mm
$d_1$	84,4 mm
$D_1$	104,3 mm
$B_1$	6 mm
$n_G$	7100 1/min / Limiting speed
$n_B$	4150 1/min / Reference speed
$C_{Or}$	182000 N / Static load rating (radial)
Bearing number	NJ2213-E-TVP2 + HJ2213-E
$C_{ur}$	33000 N / Fatigue limit load, radial
$r_{min}$	1,5 mm
$r_{a max}$	1,5 mm
$r_{1 min}$	1,5 mm

$d_{a \min}$	74 mm
$d_{a \max}$	77 mm
$D_{a \max}$	111 mm
$d_{c \min}$	87 mm
Bore Diameter (mm)	65
Outer Diameter (mm)	120
- HJ2213-E / Designation, L-section ring	HJ2213E / Designation, Lsection ring