



Bearing No. 7308 BEGAP

D	90 mm
d	40 mm
B	23 mm
a	39 mm
Bore	1.575 Inch 40 Millimeter
Noun	Bearing
Width	0.906 Inch 23 Millimeter
UNSPSC	31171531
Preload	Light
series:	73
Category	Angular Contact Ball Bearing
Size (mm)	90x40x23
Enclosure	Open
Snap Ring	No
Inventory	0.0
Width (mm)	23
Weight / LBS	1.347
Flush Ground	Yes
Mass bearing	0.62 kg
maximum rpm:	10000 RPM
Product Group	B00308
Inch - Metric	Metric
closure type:	Open
Contact Angle	40 Degree
Cage Material	Polymer
D_1	71.6 mm
d_2	49.55 mm
d_1	59.7 mm

cage material:	Nylon
Keyword String	Angular Contact
overall width:	23 mm
contact angle:	40 °
fillet radius:	1.5 mm
bore diameter:	40 mm
Bearing number	7308 BEGAP
Limiting speed	10000 r/min
finish/coating:	Uncoated
Rolling Element	Ball Bearing
Precision Class	ABEC 3 ISO P6
Reference speed	10000 r/min
Long Description	40MM Bore; 90MM Outside Diameter; 23MM Width; Open; Yes Flush Ground; Ball Bearing; Single Row of Balls; ABEC 3 ISO P6; No Filling Slot; No Snap Ring
Outside Diameter	3.543 Inch 90 Millimeter
Manufacturer URL	http://www.skf.com
Weight / Kilogram	0.61
precision rating:	ABEC 3 (ISO Class 6)
outside diameter:	90 mm
outer ring width:	23 mm
Manufacturer Name	SKF
Bore Diameter (mm)	90
r _b max.	1 mm
r _a max.	1.5 mm
D _b max.	84.4 mm
D _a max.	81 mm
d _a min.	49 mm

Number of Bearings	1 (Single)
Internal Clearance	C0-Medium
Outer Diameter (mm)	40
internal clearance:	C0
D_a - max.	81 mm
Calculation factor A	0.0173
$r_{1,2}$ min.	1.5 mm
d_a - min.	49 mm
Minimum Buy Quantity	N/A
Mounting Arrangement	Universal
$r_{3,4}$ min.	1 mm
r_a - max.	1.5 mm
r_b - max.	1 mm
Calculation factor X	0.57
Calculation factor e	1.14
D_b - max.	84.4 mm
d_1 ?	59.7 mm
row type & fill slot:	Single-Row Non-Fill Slot
D_1 ?	71.6 mm
d_2 ?	49.55 mm
Harmonized Tariff Code	8482.10.50.28
Calculation factor - X	0.35
Calculation factor - e	1.14
$r_{1,2}$ - min.	1.5 mm
$r_{3,4}$ - min.	1 mm
Number of Rows of Balls	Single Row
Manufacturer Item Number	7308 BEGAP
Basic dynamic load rating C	50 kN
radial static load capacity:	32.5 kN
radial dynamic load	50 kN

capacity:	
Basic dynamic load rating - C	50 kN
Maximum Capacity / Filling Slot	No
Calculation factor Y_0	0.52
Calculation factor Y_2	0.93
Calculation factor Y_1	0.55
Calculation factor k_r	0.1
Fatigue load limit P_u	1.37 kN
Fatigue load limit - P_u	1.4 kN
Calculation factor - k_a	1.6
Calculation factor - k_r	0.1
Calculation factor - Y_1	
Calculation factor - Y_2	0.57
Calculation factor - Y_0	0.26
Basic static load rating C_0	32.5 kN
Basic static load rating - C_0	32.5 kN