



Bearing No. 7308B

D	90 mm
d	40 mm
B	23 mm
C	23 mm
a	15.8 mm
r1	1 mm
Noun	Bearing
Bore	1.575 Inch 40 Millimeter
Width	0.906 Inch 23 Millimeter
UNSPSC	31171531
r min.	1.5 mm
Weight	0.655 Kg
ra max.	1.5 mm
da min.	49 mm
Da max.	81 mm
r1 min.	1 mm
Category	Angular Contact Ball Bearing
ra (max)	1.5 mm
Size (mm)	40x90x23
da1 (min)	49 mm
da2 (min)	45 mm
Bore Size	40 mm
Bore Type	Cylindrical Bore
Da1 (max)	81 mm
Da2 (max)	84.6 mm
ra1 (max)	1 mm
Snap Ring	No
Enclosure	Open

Inventory	0.0
Width (mm)	23
Flush Ground	No
Weight / LBS	1.44
Contact Angle	40 Degree
Inch - Metric	Metric
Product Group	B00308
Configuration	Single Row
Cage Material	Steel
Bearing number	7308B
Keyword String	Angular Contact
Rolling Element	Ball Bearing
Angle (?)	40 °
Precision Class	ABEC 1 ISO P0
Long Description	40MM Bore; 90MM Outside Diameter; 23MM Width; Open; No Flush Ground; Ball Bearing; Single Row of Balls; ABEC 1 ISO P0; No Filling Slot; No Snap Ring
Manufacturer URL	http://www.nachi.com
Outside Diameter	3.543 Inch 90 Millimeter
Manufacturer Name	NACHI
Weight / Kilogram	0.654
Static Load Rating	31,000 N
Internal Clearance	C0-Medium
Number of Bearings	1 (Single)
Bore Diameter (mm)	40
Outer Diameter (mm)	90
Dynamic Load Rating	46,000 N
Minimum Buy Quantity	N/A
Limiting Speed - Oil	8,500 rpm

Fillet Radius/Chamfer	1.5 mm
Harmonized Tariff Code	8482.10.50.28
Limiting Speed - Grease	6,300 rpm
Number of Rows of Balls	Single Row
Manufacturer Item Number	7308 B BNLS
(Grease) Lubrication Speed	6300 r/min
Basic dynamic load rating (C)	46 kN
Basic static load rating (C0)	31 kN
Maximum Capacity / Filling Slot	No