



Bearing No. 7308B

D	90 mm
d	40 mm
B	23 mm
C	23 mm
a	38.8 mm
Cu	2.00
Cr	56.0
f0	-
C0r	30.3
Noun	Bearing
Bore	1.575 Inch 40 Millimeter
a(mm)	38.8
Width	0.906 Inch 23 Millimeter
Weight	0.657 Kg
r min.	1.5 mm
UNSPSC	31171531
r(min)	1.5
da(min)	48.5
r1 min.	1 mm
Da max.	81.5 mm
r1(min)	1
Da(max)	81.5
ra max.	1.5 mm
ra(max)	1.5
da min.	48.5 mm
Category	Angular Contact Ball Bearing
Oil lub.	7300
Inventory	0.0

Enclosure	Open
Size (mm)	40x90x23
Snap Ring	No
Width (mm)	23
Bearing No.	7308B
Grease lub.	5500
Flush Ground	No
Contact Angle	40 Degree
Inch - Metric	Metric
Cage Material	Steel
Product Group	B00308
Keyword String	Angular Contact
Bearing number	7308B
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Angle (?)	40 °
(Refer.)Mass(kg)	0.657
Outside Diameter	3.543 Inch 90 Millimeter
Manufacturer URL	http://www.koyousa.com
Long Description	40MM Bore; 90MM Outside Diameter; 23MM Width; Open; No Flush Ground; Ball Bearing; Single Row of Balls; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; C0-Medium; Steel Cage; 40 Degree; 1 (Single)
Weight / Kilogram	0
Manufacturer Name	KOYO
Number of Bearings	1 (Single)
Internal Clearance	C0-Medium
Bore Diameter (mm)	40

Outer Diameter (mm)	90
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.28
Number of Rows of Balls	Single Row
(Grease) Lubrication Speed	6900 r/min
Maximum Capacity / Filling Slot	No