



**Bearing No. NJ2219**

|            |           |
|------------|-----------|
| C          | 43 mm     |
| d          | 95 mm     |
| D          | 170 mm    |
| B          | 43 mm     |
| B2         | -         |
| Cu         | 42.9      |
| Ew         | -         |
| d1         | -         |
| B1         | -         |
| Cr         | 288       |
| Fw         | 113.5 mm  |
| C0r        | 298       |
| r min.     | 2.1 mm    |
| Weight     | 3.85 Kg   |
| r(min)     | 2.1       |
| da(min)    | -         |
| db(min)    | 106       |
| db(max)    | 111       |
| dc(min)    | -         |
| r1(min)    | 2.1       |
| dd(min)    | -         |
| Da(max)    | 159       |
| Db(max)    | -         |
| Db(min)    | -         |
| r1 min.    | 2.1 mm    |
| ra(max)    | 2         |
| rb(max)    | 2         |
| Oil lub.   | 4400      |
| Size (mm)  | 95x170x43 |
| Width (mm) | 43        |

|                               |            |
|-------------------------------|------------|
| Grease lub.                   | 3300       |
| Bearing No.                   | NJ2219     |
| Bearing number                | NJ2219     |
| (Refer.)Mass(kg)              | 3.98       |
| Bore Diameter (mm)            | 95         |
| Outer Diameter (mm)           | 170        |
| (Grease) Lubrication Speed    | 3300 r/min |
| Basic static load rating (C0) | 298 kN     |
| Basic dynamic load rating (C) | 230 kN     |