



Bearing No. YSA 213-2FK + HA 2313

C	27 mm
d	55.563 mm
D	120 mm
B	43.5 mm
Size (mm)	120x55.562x65
Width (mm)	65
d <sub>3</sub>	85 mm
B <sub>1</sub>	65 mm
s <sub>1</sub>	35.3 mm
d <sub>3</sub>	85 mm
d <sub>2</sub>	82.5 mm
B <sub>1</sub>	65 mm
d <sub>1</sub>	55.562 mm
Limiting speed	3000 r/min
Bearing number	YSA 213-2FK + HA 2313
s <sub>1</sub> - ?	35.4 mm
Associated spanner	HN 12-13
Bore Diameter (mm)	120
Outer Diameter (mm)	55,562
d <sub>1</sub> ?	82.5 mm
Limiting speed <sup>1)</sup>	3000 r/min
Basic dynamic load rating C	57.2 kN
Basic dynamic load rating - C	57.2 kN
Mass bearing + adapter sleeve	2.1 kg
Calculation factor f <sub>0</sub>	15
Fatigue load limit P <sub>u</sub>	1.7 kN
Fatigue load limit - P <sub>u</sub>	1.7 kN

Calculation factor - $f_0$	15
Basic static load rating $C_0$	40 kN
Basic static load rating - $C_0$	40 kN
Recommended lock nut tightening angle ?	100 °