



**Bearing No. 7306C**

a	-3.6 mm
d	30 mm
D	72 mm
B	19 mm
C	19 mm
r1	0.6 mm
a -	3.6 mm
Width	19 mm
Weight	0.360 Kg
r min.	1.1 mm
ra max.	1 mm
Da max.	65 mm
da min.	37 mm
r1 min.	0.6 mm
ra (max)	1 mm
Da1 (max)	65 mm
Da2 (max)	67 mm
da2 (min)	37 mm
da1 (min)	37 mm
Size (mm)	30x72x19
Enclosure	Open
Bore Type	Cylindrical Bore
Bore Size	30 mm
ra1 (max)	0.6 mm
Width (mm)	19
Configuration	Single Row
Bearing number	7306C
Angle (?)	15 °
Outside Diameter	72 mm
Static Load Rating	20,400 N

Bore Diameter (mm)	30
Dynamic Load Rating	32,500 N
Outer Diameter (mm)	72
Limiting Speed - Oil	22,000 rpm
Fillet Radius/Chamfer	1.1 mm
Limiting Speed - Grease	16,000 rpm
(Grease) Lubrication Speed	16000 r/min
Basic static load rating (C0)	20,4 kN
Basic dynamic load rating (C)	32,5 kN