



Bearing No. 7306CDB

C	19 mm
d	30 mm
B	19 mm
D	72 mm
r1	0.6 mm
2B	38 mm
a -	3.6 mm
Width	19 mm
r min.	1.1 mm
Weight	0.360 Kg
ra max.	0.6 mm
r1 min.	0.6 mm
da min.	37 mm
Da max.	67 mm
ra (max)	1 mm
da1 (min)	37 mm
Bore Size	30 mm
Enclosure	Open
Bore Type	Cylindrical Bore
ra1 (max)	0.6 mm
Size (mm)	30x72x19
da2 (min)	37 mm
Da2 (max)	67 mm
Da1 (max)	65 mm
Width (mm)	19
Configuration	Duplex
Bearing number	7306CDB
Angle (?)	15 °
Outside Diameter	72 mm
Static Load Rating	40,500 N

Bore Diameter (mm)	30
Dynamic Load Rating	52,500 N
Outer Diameter (mm)	72
Limiting Speed - Oil	18,000 rpm
Fillet Radius/Chamfer	1.1 mm
Limiting Speed - Grease	13,000 rpm
(Grease) Lubrication Speed	13000 r/min
Basic dynamic load rating (C)	52,5 kN
Basic static load rating (C0)	40,5 kN