



Bearing No. NUP 2326 ECML

F	167 mm
d	130 mm
D	280 mm
B	93 mm
Size (mm)	280x130x93
Width (mm)	93
Mass bearing	29.5 kg
d <sub>1</sub>	181 mm
D <sub>1</sub>	235.2 mm
Limiting speed	4500 r/min
Bearing number	NUP 2326 ECML
Reference speed	2400 r/min
Limiting value e	0.3
d <sub>a</sub> min.	147 mm
D <sub>a</sub> max.	261.4 mm
r <sub>a</sub> max.	3 mm
Bore Diameter (mm)	280
d <sub>b</sub> min.	184 mm
Outer Diameter (mm)	130
Axial load factor Y	0.4
r <sub>a</sub> - max.	3 mm
D <sub>a</sub> - max.	261.4 mm
d <sub>b</sub> - min.	184 mm
d <sub>a</sub> - min.	147 mm
r <sub>1,2</sub> min.	4 mm
r <sub>3,4</sub> min.	4 mm
d <sub>1</sub> ?	181 mm
D <sub>1</sub> ?	235.2 mm
r <sub>1,2</sub> - min.	4 mm
r <sub>3,4</sub> - min.	4 mm

Basic dynamic load rating C	1060 kN
Basic dynamic load rating - C	1060 kN
Fatigue load limit $P_u$	137 kN
Calculation factor $k_r$	0.38
Calculation factor - $k_r$	0.38
Fatigue load limit - $P_u$	137 kN
Basic static load rating $C_0$	1250 kN
Basic static load rating - $C_0$	1250 kN