



Bearing No. 7305 BEY

a	26.8 mm
d	25 mm
D	62 mm
B	17 mm
Bore	0.984 Inch 25 Millimeter
Noun	Bearing
Width	0.669 Inch 17 Millimeter
UNSPSC	31171531
series:	73
Category	Angular Contact Ball Bearing
Enclosure	Open
Snap Ring	No
Size (mm)	62x25x17
Inventory	0.0
Width (mm)	17
maximum rpm:	14000 RPM
Flush Ground	No
Mass bearing	0.23 kg
Contact Angle	40 Degree
Cage Material	Brass
closure type:	Open
Product Group	B00308
Inch - Metric	Metric
d ₁	39.65 mm
d ₂	32.38 mm
D ₁	48.25 mm
Limiting speed	14000 r/min

Keyword String	Angular Contact
fillet radius:	1 mm
contact angle:	40 °
overall width:	17 mm
cage material:	Brass
bore diameter:	25 mm
Bearing number	7305 BEY
finish/coating:	Uncoated
Rolling Element	Ball Bearing
Reference speed	14000 r/min
Precision Class	ABEC 1 ISO P0
Long Description	25MM Bore; 62MM Outside Diameter; 17MM Width; Open; No Flush Ground; Ball Bearing; Single Row of Balls; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; C0-Medium; Brass Cage; 40 Degree; 1 (Single)
Outside Diameter	2.441 Inch 62 Millimeter
Manufacturer URL	http://www.skf.com
precision rating:	ABEC 3 (ISO Class 6)
outside diameter:	62 mm
Manufacturer Name	SKF
outer ring width:	17 mm
Weight / Kilogram	0.25
Internal Clearance	C0-Medium
r _b max.	0.6 mm
r _a max.	1 mm
D _b max.	57.8 mm
D _a max.	55 mm
d _a min.	32 mm

Bore Diameter (mm)	62
Number of Bearings	1 (Single)
internal clearance:	C0
Outer Diameter (mm)	25
D_b - max.	57.8 mm
D_a - max.	55 mm
r_b - max.	0.6 mm
Calculation factor X	0.57
Calculation factor e	1.14
Calculation factor A	0.00391
d_a - min.	32 mm
r_a - max.	1 mm
Minimum Buy Quantity	N/A
$r_{3,4}$ min.	0.6 mm
$r_{1,2}$ min.	1.1 mm
D_1 ?	48.25 mm
d_1 ?	39.75 mm
d_2 ?	32.38 mm
row type & fill slot:	Single-Row Non-Fill Slot
$r_{3,4}$ - min.	0.6 mm
Harmonized Tariff Code	8482.10.50.28
$r_{1,2}$ - min.	1.1 mm
Calculation factor - X	0.35
Calculation factor - e	1.14
Number of Rows of Balls	Single Row
Manufacturer Item Number	7305 BEY
Basic dynamic load rating C	24.2 kN
radial static load capacity:	15.6 kN
radial dynamic load capacity:	26 kN

Basic dynamic load rating - C	24.2 kN
Maximum Capacity / Filling Slot	No
Fatigue load limit P_u	0.6 kN
Calculation factor k_r	0.1
Calculation factor Y_1	0.55
Calculation factor Y_2	0.93
Calculation factor Y_0	0.52
Calculation factor - k_r	0.1
Calculation factor - Y_2	0.57
Calculation factor - Y_1	
Calculation factor - k_a	1.6
Fatigue load limit - P_u	0.6 kN
Calculation factor - Y_0	0.26
Basic static load rating C_0	14 kN
Basic static load rating - C_0	14 kN