



## Bearing No. 483/472

|                                 |                 |
|---------------------------------|-----------------|
| R                               | 3,6 mm          |
| d                               | 63,5 mm         |
| D                               | 120 mm          |
| T                               | 29,794 mm       |
| B                               | 29,007 mm       |
| C                               | 24,237 mm       |
| r                               | 2 mm            |
| Da                              | 114 mm          |
| Ab                              | 2,2 mm          |
| Aa                              | 1,5 mm          |
| Db                              | 107 mm          |
| da                              | 72 mm           |
| db                              | 78 mm           |
| a -                             | 4,1 mm          |
| Weight                          | 1,46 Kg         |
| Size (mm)                       | 63.5x120x29.794 |
| Width (mm)                      | 29,794          |
| Factor (K)                      | 1,52            |
| Factor (G1)                     | 77,2            |
| Factor (Cg)                     | 0,0293          |
| Factor (G2)                     | 23              |
| Bearing number                  | 483/472         |
| Bore Diameter (mm)              | 63,5            |
| Outer Diameter (mm)             | 120             |
| Calculation factor (e)          | 0,38            |
| Basic static load rating (C0)   | 186 kN          |
| Basic dynamic load rating (C1)  | 133 kN          |
| Basic dynamic load rating (C90) | 34,4            |

|                                  |      |
|----------------------------------|------|
| Basic dynamic load rating (Ca90) | 22,7 |
|----------------------------------|------|