



Bearing No. 6226

r	3
d	130 mm
D	230 mm
B	40 mm
C	40 mm
ra	2.5
C0	146
fo	14.5
B_	40
D_	230
Z_	10
DI_	148.25
D_a	217
DE_	211.75
DA_	31.75
SRE	16.43
SRI	16.43
SDM_	180
SREN	-0.065
mass	5.96
Bore	5.118 Inch 130 Millimeter
SBRG	2
SRIX	0.065
KBRG	6101
Noun	Bearing
SRIN	-0.065
bomp	0
SREX	0.065
yobi	6226

UNSPSC	31171504
C_conv	167000
Weight	5,96 Kg
da max	157 mm
LangID	1
da min	143
r min.	3 mm
ALPHA_	0
ra max.	2,5 mm
Oil rpm	3000
Da max.	217 mm
hidYobi	6226
GRS rpm	2400
series:	62
da min.	143 mm
hidTable	ecat_NSRDGB
Category	Single Row Ball Bearing
Snap Ring	No
Size (mm)	130x230x40
Enclosure	Open
Inventory	0.0
bore type:	Round
Prod_Type3	DGBB_SR_OT
Width (mm)	40
Weight / LBS	5.8
maximum rpm:	3000 RPM
Inch - Metric	Metric
Cage Material	Steel
closure type:	Open
Product Group	B00308
Bearing number	6226
bore diameter:	130 mm

fillet radius:	3 mm
Keyword String	Ball
cage material:	Steel
overall width:	40 mm
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
finish/coating:	Uncoated
Long Description	130MM Bore; 230MM Outside Diameter; 40MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Manufacturer URL	http://www.nskamericas.com
Outer Race Width	1.575 Inch 40 Millimeter
Outside Diameter	9.055 Inch 230 Millimeter
Weight / Kilogram	5.8
precision rating:	ABEC 1 (ISO Class Normal)
outer ring width:	40 mm
Manufacturer Name	NSK
outside diameter:	230 mm
Bore Diameter (mm)	130
Internal Clearance	C0-Medium
Outer Diameter (mm)	230
internal clearance:	C0
Minimum Buy Quantity	N/A
static load capacity:	146000 N
row type & fill slot:	Single Row Non-Fill Slot
Harmonized Tariff Code	8482.10.50.68
dynamic load capacity:	167000 N

(Oil) Lubrication Speed	3 000 r/min
Manufacturer Item Number	6226
Internal Special Features	No
(Grease) Lubrication Speed	2 400 r/min
operating temperature range:	Maximum of +250 °F
Basic static load rating (C0)	146 kN
Basic dynamic load rating (C)	167 kN
Maximum Capacity / Filling Slot	No